

T430 High Yield Print Cartridge

Printer: T430

Declaration of Yield: **Average Cartridge Yield 12000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 14140
Std Dev 744
90% Lower Confidence 13814

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

| | <u>start</u> | <u>stop</u> |
|--|--------------|---------------------------------|
| Date tested | 11-Oct-2004 | 14-Oct-2004 |
| Number of cartridges in testing | | 16 |
| Qty. of cartridges used in calculation | | 16 |
| Shake Procedure | 1st shake | At fade |
| | 2nd shake | At fade |
| Print mode | | Continuous |
| Number of printers tested | | 4 |
| Media used | | Boise Cascade - 20# - Letter |
| Paper feed orientation | | Short Edge Feed (SEF) |
| Driver version | | T430 G9 |
| Operating system | | Windows 98 |
| Application software | | Acrobat version 6.01 |
| Test page version | | Standard Testpage (PDF 1.3).pdf |

| Cartridge testing data: | | Temperature | | | Humidity | | | Cartridge Yield | Cart used in Calculation |
|-------------------------|---------|-------------|-----|-----|----------|-----|-----|-----------------|--------------------------|
| Cartridge | Printer | Avg | Max | Min | Avg | Max | Min | | |
| CAD042298185 | 79203ZK | 74 | 76 | 74 | 45 | 49 | 40 | 14,130 | Y |
| CAD042298052 | 79208T2 | 74 | 76 | 74 | 45 | 49 | 40 | 14,270 | Y |
| CAD042298158 | 79208TG | 74 | 76 | 74 | 45 | 49 | 40 | 12,992 | Y |
| CAD042298176 | 79208T9 | 74 | 76 | 74 | 45 | 49 | 40 | 13,417 | Y |
| CAD041960778 | 79203ZK | 73 | 75 | 71 | 51 | 56 | 43 | 15,268 | Y |
| CAD041961415 | 79208T2 | 73 | 75 | 71 | 51 | 56 | 43 | 14,855 | Y |
| CAD041961423 | 79208TG | 73 | 75 | 71 | 51 | 56 | 43 | 15,202 | Y |
| CAD041960743 | 79208T9 | 73 | 75 | 71 | 51 | 56 | 43 | 13,948 | Y |
| CAD042010495 | 79203ZK | 72 | 72 | 70 | 56 | 58 | 53 | 14,375 | Y |
| CAD042010569 | 79208T2 | 72 | 72 | 70 | 56 | 58 | 53 | 14,668 | Y |
| CAD042010477 | 79208TG | 72 | 72 | 70 | 56 | 58 | 53 | 14,535 | Y |
| CAD042010223 | 79208T9 | 72 | 72 | 70 | 56 | 58 | 53 | 14,298 | Y |
| CAD042010559 | 79203ZK | 72 | 74 | 70 | 51 | 56 | 47 | 13,966 | Y |
| CAD042298093 | 79208T2 | 72 | 74 | 70 | 51 | 56 | 47 | 14,365 | Y |
| CAD042298218 | 79208TG | 72 | 74 | 70 | 51 | 56 | 47 | 12,671 | Y |
| CAD041960754 | 79208T9 | 72 | 74 | 70 | 51 | 56 | 47 | 13,276 | Y |

Comments and or exceptions: