

T520/T522 Print Cartridge

Printer: T522

Declaration of Yield: **Average Cartridge Yield 20000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 21469
Std Dev 466
90% Lower Confidence 21227

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 17-Jan-2005 stop 21-Jan-2005

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	7.4.1
Operating system	Windows 2000
Application software	Adobe Acrobat version 5
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature			Humidity				
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min	Cartridge Yield	Cart used in Calculation
CAX043501FD5D	9903G65	74	75	74	48	51	48	20,709	Y
CAX043501FDBD	E004876	74	75	74	48	51	48	21,168	Y
CAX043510E10D	E004877	74	75	74	48	51	48	21,229	Y
CAX04351085FD	E004915	74	75	74	48	51	48	21,110	Y
CAX0435108ABD	9903G65	74	75	74	48	49	48	21,397	Y
CAX0435204BDD	E004876	74	75	74	48	49	48	21,238	Y
CAX0435204BAD	E004877	74	75	74	48	49	48	22,452	Y
CAX0435108A1D	E004915	74	75	74	48	49	48	21,318	Y
CAX0435204B8D	9903G65	74	75	74	48	49	48	21,844	Y
CAX0435109ABD	E004876	74	75	74	48	49	48	21,752	Y
CAX043501FCDD	E004877	74	75	74	48	49	48	21,980	Y
CAX043501FDCC	E004915	74	75	74	48	49	48	21,426	Y