

T630, T632, T634 Print Cartridge

Printer: T630

Declaration of Yield: **Average Cartridge Yield 5000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 6109
Std Dev 412
90% Lower Confidence 5895

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 28-Sep-2004 stop 29-Sep-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low
	2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	8.4.0.0
Operating system	Windows 2000
Application software	Adobe Acrobat version 5.0
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAX042029550D	991G23K	75	75	74	51	52	51	5,380	Y
CAX042066319D	991G3TC	75	75	74	51	52	51	6,430	Y
CAX041658921D	991G3T3	75	75	74	51	52	51	5,974	Y
CAX041630112D	991G23X	75	75	74	51	52	51	6,334	Y
CAX041638438D	991G23K	75	75	75	51	51	51	5,910	Y
CAX042029562D	991G3TC	75	75	75	51	51	51	5,497	Y
CAX042066299D	991G3T3	75	75	75	51	51	51	6,269	Y
CAX041658058D	991G23X	75	75	75	51	51	51	6,036	Y
CAX041658910D	991G23K	74	75	74	51	52	51	5,992	Y
CAX041637876D	991G3TC	74	75	74	51	52	51	6,619	Y
CAX042029571D	991G3T3	74	75	74	51	52	51	6,776	Y
CAX042066264D	991G23X	74	75	74	51	52	51	6,088	Y

Comments and or exceptions: