

T632, T634 Extra High Yield Print Cartridge

Printer: T634

Declaration of Yield: **Average Cartridge Yield 32000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 33692
Std Dev 1614
90% Lower Confidence 32856

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 4-Oct-2004 stop 12-Oct-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low
	2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	8.4.0.0
Operating system	Windows 2000
Application software	Adobe Acrobat version 5.0
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAX042199716	9914W10	75	75	74	48	48	47	33,346	Y
CAX042058790	9914W1H	75	75	74	48	48	47	31,683	Y
CAX042077307	9914W5W	75	75	74	48	48	47	31,986	Y
CAX041839807	9914W6Y	75	75	74	48	48	47	35,245	Y
CAX041838865	9914W10	74	75	74	48	48	47	36,906	Y
CAX042199750	9914W1H	74	75	74	48	48	47	33,554	Y
CAX042198801	9914W5W	74	75	74	48	48	47	33,837	Y
CAX042077150	9914W6Y	74	75	74	48	48	47	33,575	Y
CAX042076344	9914W10	74	75	74	48	49	47	35,472	Y
CAX041838244	9914W1H	74	75	74	48	49	47	32,423	Y
CAX042199720	9914W5W	74	75	74	48	49	47	31,836	Y
CAX042058061	9914W6Y	74	75	74	48	49	47	34,444	Y

Comments and or exceptions: