



see below for additional pn's

**T640, T642, T644 High Yield Print Cartridge**

Printer: T642

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>6000</b>	<b>standard pages</b>
	<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 7761  
**Std Dev** 426  
**90% Lower** 7497  
**Confidence**

**For questions concerning testing contact:**  
Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

	<b><u>start</u></b>	<b><u>stop</u></b>
<b>Date tested</b>	17-Apr-2005	18-Apr-2005

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	3
Media used	Boise Cascade - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	T642 version 1
Operating system	Windows 2000
Application software	Acrobat version 6.01
Test page version	Down load Free__19752 Test Chart.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS050910450	PL3-104-M	74	75	73	52	55	49	6,781	Y
CAS050910538	PL3-104-M	74	75	73	52	55	49	7,401	Y
CAS050910478	PL3-104-M	74	75	73	52	55	49	7,701	Y
CAS050910474	PL3-107-M	74	75	73	52	55	49	8,100	Y
CAS050910467	PL3-107-M	74	75	73	52	55	49	7,901	Y
CAS050910530	PL3-107-M	74	75	73	52	55	49	7,921	Y
CAS050910526	PL3-110-M	74	75	73	52	55	49	8,000	Y
CAS050910510	PL3-110-M	74	75	73	52	55	49	8,060	Y
CAS050910473	PL3-110-M	74	75	73	52	55	49	7,981	Y

**Comments and or exceptions:**

also covers:

64016SE	64036SE
64017SR	64037SR
64018SL	64038SL